

FANYUAN INSTRUMENT (HF) CO., LTD. DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD.

ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088

TEL: +86-551-65232508 FAX: +86-551-65232507 Email: sales@hkdowell.com Website: http://www.fyichina.com.cn

DW5071 Fabric Down-proof Impact Tester



MODEL NO.

DW5071

APPLICATION



FANYUAN INSTRUMENT (HF) CO., LTD. DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD.

ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088

TEL: +86-551-65232508 FAX: +86-551-65232507 Email: sales@hkdowell.com

Website: http://www.fyichina.com.cn

DW5071 Fabric down proof impact tester adopt impact method to test puncture resistance performance for winter clothes, quilt lining which fill with fiber or feather or both.

A cylindrical cushion is made from the fabric to be tested for its down-proof properties and is filled with a given amount of feather and down material or its mixtures. Sliding on an inclined plane, this cushion is moved by means of a pinned bar against a pinned plate, and is thus compressed. After the impact, the cushion is rolled back following the backward-moving pinned impact rake, and recovers its shape. This procedure is continuously repeated until a certain number of impacts are reached.

STANDARDS

STANDARDS

BS EN 12132-2

Note: this tester can conform to but not limit to the standards above, for more standards conformance, please contact us.

FEATURES:

- Steel frame, firm and stable;
- Adopts Crank-rocker mechanism to make the moveable plate move as 35 times/min;
- Two plates: one is fixed with on firmly mounted pin, and the other is moveable which have 3 pins on it to accomplish impact;
- LED display and the counter can be preset;
- Automatically stopped by the counter after reaches the preset value.

KEY SPECIFICATIONS

• Inclined plate angle 20°

Impact frequency
35 impacts per minute

Stroke 500mm

• Pin length 80mm diameter Φ 15mm

• Fillings Feather, feather and down or both mixtures

• Counter 0~99999



FANYUAN INSTRUMENT (HF) CO., LTD. DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD.

ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088

TEL: +86-551-65232508 FAX: +86-551-65232507 Email: sales@hkdowell.com Website: http://www.fyichina.com.cn

DisplayLED

• Dimension 800x250x500mm

Weight Approx.75kg

• Power supply AC 380V 50Hz

STANDARD CONFIGURATION

No.	Item	Quantity
1	Main machine	1set
2		

OPTIONAL ACCESSORIES

No.	Item
1	HZT-A200 Electronic balance(200G,0.01g)
2	BZGY908 Color Assessment Cabinet