

FANYUAN INSTRUMENT (HF) CO., LTD. DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD. ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088 TEL: +86-551-65232508 FAX: +86-551-65232507 Email: sales@hkdowell.com Website: http://www.fyichina.com.cn

YG021D ELECTRONIC SINGLE END YARN STRENGTH TESTER



We offer reliable and stable products, their precise technical data, and timely and enthusiastic service High performance and low expense



MODEL NO.

YG021D

APPLICATION

Single End Yarn Strength Tester is used to determine the breaking load and extension of single yarns, core-spun yarn etc. up-to 50000 centi-grams force.

RELATED STANDARDS

STANDARDS	ISO 2062	ASTM D2256	BS1932.Pt.2
	DIN53842.1, DIN53835.2	KS K0409	

Note: this tester can conform to but not limit to the standards above, for more standards conformance, please contact us.

FEATURES

- Use 16bit Industry-grade MCU, large blue LCD panel (Jingcai, Chinese Taiwan), operator simply inputs test data by many kinds of characters, real time display elongation diagram and test data.
- Accurately Positioning system with servo motor (Panasonic, Japan) and ball screw lead support, low noise and run smoothly;
- Choose English or Chinese displaying mode obviously, with memory function when power interrupt, and up to 300 groups data storage;
- Operator can use LCD control panel to control the machine and print out testing report by stylus printer without PC;
- Test function includes elongation with constant speed, load at specified elongation, elongation at specified load, tear and peel etc.
- Gauge length and tension speed presettable;
- Able to set pre-tensile force;
- Many kinds of clamp are selectable according to requirements test standards, including pneumatic clamps.

KEY SPECIFICATION

- Capacity and resolution 5000cN, 1.0cN; 12000cN, 1.0cN; 50000cN, 0.1N
- Accuracy $\pm 0.5\%$



FANYUAN INSTRUMENT (HF) CO., LTD. DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD. ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088 TEL: +86-551-65232508 FAX: +86-551-65232507 Email: sales@hkdowell.com Website: http://www.fyichina.com.cn

- Gauge length
- 50~500mm (digital preset)
- Max elongation (with grips) 750mm
- Speed 50~1000mm/min (digital preset)
 - Position accuracy 0.1mm
- Preset tension mode A: adding weight; B: Set by procedure
- Power supply AC220V±10%, 50Hz, 100W
- Instrument Size $550 \times 510 \times 1380$ mm (L×W×H)
- Weight 95kg

STANDARD CONFIGURATION

No.		Item		Quantity
1	Main machine with PC port			1set
2	Stylus printer		\cap	1set
3	Manual clamp		\mathbf{V}	1 set

OPTIONAL ACCESSORIES

No.	\checkmark \diamond	Item

1 Personal computer with software