



DW9520 FREEZING LEATHER FLEXING TESTER



Leather clamp



Leather & shoe clamp



FANYUAN INSTRUMENT (HF) CO., LTD.
DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD.
ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088
TEL: +86-551-65232508
FAX: +86-551-65232507
Email: sales@hkdownell.com
Website: http://www.fyichina.com.cn

MODEL NO.

DW9520 (the former model HY-769L)

Application:

Specially designed to test the behavior of various materials in a cold environment to ensure the suitability for use in cold climate. Based the testing demand, adjust the beater and flexing grip, then load to the desire position. It can be used to test rubber, leather, plastic, PU leather, etc. Installation of bending test, flexing test and impact test are available.

Related Standards:

STANDARDS	ASTM D1790,1593,1052	JIS K6545	ISO 20344	CNS 7705
-----------	----------------------	-----------	-----------	----------

Note: this tester can conform to but not limit to all the standards above, for more standards conformance, please contact us.

Features:

- SUS#304 Stainless steel of inner and outside of chamber;
- Bally flexing clamp is configuration, shoe flexing clamp also can be added in chamber;
- Other clamp can be customized;
- Easy installation and use;
- Adopt double layer high expansionary seal between door and chamber body to ensure enclosed of testing area;
- Use whole sealing compressor (Tecumseh, France), cascade refrigeration cooling method;
- Thermal isolation material is made from high density glass fiber cotton;
- Adapts environment protection refrigerant.

Key Specification:

- | | |
|------------------------|--------------------|
| ● Angle of flexing | 22.5° |
| ● Speed | 100±5 cpm |
| ● Test sheet | 70×45mm |
| ● Working position | 12 (bally flexing) |
| ● Controller box | RCK(Japan) PID |
| ● Temperature range | RT~ -30C° |
| ● Temperature accuracy | ±0.3 C° |



FANYUAN INSTRUMENT (HF) CO., LTD.
DOWELL SCIENCE AND TECHNOLOGY (HK) CO., LTD.
 ADD: Tianyuan Road 9#, High-tech Zone, Hefei City, China Postal Code: 230088
 TEL: +86-551-65232508
 FAX: +86-551-65232507
 Email: sales@hkdownell.com
 Website: http://www.fyichina.com.cn

- | | |
|--|--|
| <ul style="list-style-type: none"> ● Counter ● Cooling rate ● Power consumption ● Power supply ● Working chamber size ● Dimensions ● Weight | LCD 0~999,999
RT~ -30C° with 60 min
4-6KW
AC220V 50HZ or AC 380V 50HZ
600mm×600mm×550mm(L×W×H)
1100mm×1050mm×1600mm(L×W×H)
420kg |
|--|--|

Standard configuration:

No.	Item	Quantity
1	Main machine	1 set
2	12 position bally feather flexing clamp	1 set

Optional Accessories:

No.	Item
1	5 position bally feather flexing clamp (22.5° 100cpm)
2	2 position shoe bending clamp (30~90° 100cpm)
3	2 position shoe flexing clamp (90° 100cpm)